NSN 5320-01-490-7384

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.482 inches and 0.502 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

F-22

Grip Length:

0.1875 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

7060 double pounds per square inch

Product Name:

Eddie-bolt 2 pin

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-490-7384

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

