## NSN 5320-01-491-9423

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-491-9423



### **Thread Class:** 3a **Thread Direction: Right-hand** Fastener Length: Between 2.050 inches and 2.070 inches Head Style: Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches Shank Diameter: Between 0.4990 inches and 0.4995 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, thunderbolt ii, a-10

Grip Length:

Between 1.370 inches and 1.380 inches

#### Thready Qty Per Inch (tpi):

20

#### **Thread Size:**

0.125 inches

Material:

Steel comp xm-13

#### Material Specification:

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-491-9423

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

