NSN 5320-01-492-4492

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-492-4492

Thread Direction:

Right-hand

Head Style:

Hexagon

Head Height:

Between 0.130 inches and 0.135 inches

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Expansion Device:

Break head

Lubrication:

Cetyl alcohol or paraffin wax or dry film

Grip Length:

Between 0.345 inches and 0.406 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Product Name:

Fasteners

Special Features:

Drive nut steel with corrosion retardent coating, color coded blue; locking feature- three indentations located 120 degrees apart on the periphery of the nut component

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams5641 assn

standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

NSN 5320-01-492-4492

Blind Rivet - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.

