# NSN 5320-01-492-4580

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-492-4580



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.535 inches and 1.555 inches

### Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3640 inches and 0.3680 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.585 inches and 0.620 inches

Lubrication:

Solid film

# **End Application:**

A-10 aircraft

# Grip Length:

Between 0.995 inches and 1.005 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

19100 pounds per square inch

### Thread Size:

0.375 inches

### Shear Strength:

32400 double pounds per square inch

#### Material:

Steel comp xm-13

### **Material Specification:**

Ams 5629 assn standard single material response

# **Thread Series Designator:**

Unjf

# Specification Data:

73197-hl846 manufacturers standard

# Shelf Life:

N/a

# NSN 5320-01-492-4580

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

