## NSN 5320-01-492-4580

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

За

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-492-4580

I hread Direction:
Right-hand
Fastener Length:
Between 1.535 inches and 1.555 inches
Head Style:
Err-090
Head Height:
Between 0.130 inches and 0.140 inches
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3640 inches and 0.3680 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.585 inches and 0.620 inches
Lubrication:
Solid film
End Application:
A-10 aircraft
Grip Length:
Between 0.995 inches and 1.005 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
19100 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
32400 double pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl846 manufacturers standard
Shelf Life:

## NSN 5320-01-492-4580

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0