## NSN 5320-01-492-4612

View Online at https://aerobasegroup.com/nsn/5320-01-492-4612

Pin-rivet - Page 1 of 2



**Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.000 inches and 2.020 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4672 inches and 0.4682 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.660 inches and 0.695 inches Lubrication: Solid film **End Application:** A-10 aircraft **Grip Length:** Between 1.370 inches and 1.380 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 25800 pounds per square inch **Thread Size:** 0.4375 inches **Shear Strength:** 43100 double pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 

73197-hl846 manufacturers standard

Shelf Life:

N/a

## NSN 5320-01-492-4612

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0