

View Online at <https://aerobasegroup.com/nsn/5320-01-492-4614>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.250 inches and 2.260 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.150 inches and 0.160 inches

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4672 inches and 0.4682 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.660 inches and 0.695 inches

**Lubrication:**

Solid film

**End Application:**

A-10 aircraft

**Grip Length:**

Between 1.620 inches and 1.630 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

25800 pounds per square inch

**Thread Size:**

0.4375 inches

**Shear Strength:**

43100 double pounds per square inch

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl846 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0