## NSN 5320-01-492-4638

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-492-4638

Tilleda Direction.
Right-hand
Fastener Length:
Between 1.625 inches and 1.645 inches
Head Style:
Err-090
Head Height:
Between 0.150 inches and 0.160 inches
Width Between Flats:
Between 0.1895 inches and 0.1930 inches
Shank Diameter:
Between 0.4360 inches and 0.4370 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.641 inches and 0.676 inches
Lubrication:
Solid film
End Application:
A-10 aircraft
Grip Length:
Between 0.995 inches and 1.005 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
25800 pounds per square inch
Thread Size:
0.4375 inches
Shear Strength:
37500 double pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl646 manufacturers standard
Shelf Life:
N/a

## NSN 5320-01-492-4638

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0