NSN 5320-01-492-4645

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-492-4645

| Fastener Length: |
|---|
| Between 1.4375 inches and 1.4575 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.150 inches and 0.160 inches |
| Width Between Flats: |
| Between 0.1895 inches and 0.1930 inches |
| Shank Diameter: |
| Between 0.4360 inches and 0.4370 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.641 inches and 0.676 inches |
| Lubrication: |
| Solid film |
| End Application: |
| A-10 aircraft |
| Grip Length: |
| Between 0.8075 inches and 0.8175 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 25800 pounds per square inch |
| Thread Size: |
| 0.4375 inches |
| Shear Strength: |
| 37500 double pounds per square inch |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 73197-hl646 manufacturers standard |
| Shelf Life: |
| N/a |

NSN 5320-01-492-4645

Pin-rivet - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0