
NSN 5320-01-492-4649

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.300 inches and 2.320 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Solid film

End Application:

A-10 aircraft

Grip Length:

Between 1.620 inches and 1.630 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

34300 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

49100 double pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hl646 manufacturers standard

Shelf Life:

N/a

NSN 5320-01-492-4649

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

