## NSN 5320-01-492-4803

Pin-rivet - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-492-4803

Thread Direction:
Right-hand
Fastener Length:
Between 1.1775 inches and 1.1975 inches
Head Style:
Err-090
Head Height:
Between 0.178 inches and 0.188 inches
Width Between Flats:
Between 0.2207 inches and 0.2242 inches
Shank Diameter:
Between 0.4985 inches and 0.4995 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.735 inches and 0.770 inches
Lubrication:
Solid film
End Application:
A-10 aircraft
Grip Length:
Between 1.187 inches and 1.188 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
34300 pounds per square inch
Thread Size:
0.500 inches
Shear Strength:
49100 double pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hl646 manufacturers standard
Shelf Life:
N/a

## NSN 5320-01-492-4803

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0