NSN 5320-01-492-9785Blind Rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-01-492-9785 |
|---|
| Fastener Length: |
| Between 1.185 inches and 1.246 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.311 inches and 0.312 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| Between 0.626 inches and 0.635 inches |
| Expansion Device: |
| Threaded stem |
| Lubrication: |
| Dry film or cetyl alcohol or paraffin wax |
| Grip Length: |
| Between 0.595 inches and 0.656 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single |
| material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |