

View Online at <https://aerobasegroup.com/nsn/5320-01-493-3276>

Thread Direction:

Right-hand

Head Style:

Hexagon

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Cetyl alcohol or paraffin wax or dry film

Grip Length:

Between 0.657 inches and 0.719 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Product Name:

Fasteners

Special Features:

Drive nut steel with corrosion retardent coating, color coded blue; locking feature; prevailing locking torque; fractional diameter

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams5641 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.