

View Online at <https://aerobasegroup.com/nsn/5320-01-493-3280>

**Thread Direction:**

Right-hand

**Head Style:**

Hexagon

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Cetyl alcohol or paraffin wax or dry film

**Grip Length:**

Between 0.782 inches and 0.844 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Product Name:**

Fasteners

**Special Features:**

Drive nut steel with corrosion retardent coating, color coded blue; locking feature; prevailing locking torque; fractional diameter

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Passivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.