

View Online at <https://aerobasegroup.com/nsn/5320-01-493-8095>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.1875 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.0791 inches and 0.0806 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Grip Length:**

Between 0.1885 inches and 0.1895 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

6125 double pounds per square inch

**Countersink Angle:**

45.0 degrees

**Special Features:**

180.000-200.000 psi tensile per mil-h-6875; protruding tension head

**Material:**

Steel

**Material Specification:**

Mil-s-500, mil-s-5626 or mil-s-6049 military specification all material responses

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2, federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-500 spec.