

View Online at <https://aerobasegroup.com/nsn/5320-01-493-8097>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.3281 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.160 inches and 0.180 inches

Shank Diameter:

Between 0.1270 inches and 0.1295 inches

Shank Style:

Head Major Diameter:

Between 0.4844 inches and 0.4894 inches

Grip Length:

Between 0.3266 inches and 0.3276 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3125 inches

Shear Strength:

21070 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

108, 000-180, 000 psi shea (180, 000 psi tensile) per ams-h-6875; hi-lok hi-tigue pin, 100 degree flush crown shear head, alloy steel, 1/16 grip variation- 1/64 ovs

Material:

Steel

Material Specification:

Mil-s-5626 or mil-s-6049 military specification all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2, federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.