## NSN 5320-01-494-5135

Pin-rivet - Page 1 of 2

**Thread Class:** 

3a

View Online at https://aerobasegroup.com/nsn/5320-01-494-5135



## **Thread Direction: Right-hand** Fastener Length: Between 1.108 inches and 1.128 inches Head Style: Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.1890 inches and 0.1895 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: 0.3813 inches **End Application:** F-22 Grip Length: 0.8125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 4350 pounds per square inch **Thread Size:** 0.1900 inches Shear Strength: 7060 double pounds per square inch **Countersink Angle:** 100.0 degrees **Product Name:** Eddie-bolt 2 pin Material: Nickel alloy 718 Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-01-494-5135

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

