NSN 5320-01-494-5136

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-494-5136



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.920 inches and 0.940 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.3813 inches

End Application:

F-22

Grip Length:

0.6250 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.1900 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Eddie-bolt 2 pin

Material:

Nickel alloy 718

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-494-5136

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

