

View Online at <https://aerobasegroup.com/nsn/5320-01-495-5975>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.574 inches and 0.594 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 0.183 inches and 0.193 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 double pounds per square inch

Product Name:

Pin-riquet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear specification no 294 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0