## NSN 5320-01-495-7666

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-495-7666 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.2807 inches **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches **End Application:** Aircraft, thunderbolt ii, a-10 **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Special Features:** Pb within p/n refers to cut-plate with lubricant; finish color bronze Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A528u0

No

**Demilitarization:** 

## NSN 5320-01-495-7666

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-s-5000 spec.