NSN 5320-01-495-7963

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-495-7963
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Bronze
Fastener Length:
Between 0.885 inches and 0.905 inches
Head Style:
Err-090
Head Height:
Between 0.059 inches and 0.069 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2797 inches and 0.2807 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.387 inches and 0.412 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
A-10; thunderbolt
Grip Length:
0.505 inches
Thready Qty Per Inch (tpi):
28
Thread Size:
0.250 inches
Special Features:
Pb within p/n refers to cut-place with lubricant; finish color bronze
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740
Material Specification:
Mil-s-5000 military standard 1st material response or mil-s-5626 military standard 2nd material response or mil-s-6049 military standard 3rd
material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-495-7963

Pin-rivet - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.