NSN 5320-01-495-7963

Pin-rivet - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5320-01-495-7963 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Identification Code Color: |
| Bronze |
| Fastener Length: |
| Between 0.885 inches and 0.905 inches |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.059 inches and 0.069 inches |
| Width Between Flats: |
| Between 0.0947 inches and 0.0967 inches |
| Shank Diameter: |
| Between 0.2797 inches and 0.2807 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.387 inches and 0.412 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| End Application: |
| A-10; thunderbolt |
| Grip Length: |
| 0.505 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Thread Size: |
| 0.250 inches |
| Special Features: |
| Pb within p/n refers to cut-place with lubricant; finish color bronze |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 |
| Material Specification: |
| Mil-s-5000 military standard 1st material response or mil-s-5626 military standard 2nd material response or mil-s-6049 military standard 3rd |
| material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator: |

Unjf

NSN 5320-01-495-7963

Pin-rivet - Page 2 of 2



| Shelf | Life: |
|-------|-------|
| N/a | |

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.