NSN 5320-01-495-8690

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-495-8690

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 3.897 inches and 3.902 inches

Head Style:

Flush countersunk

Shank Diameter:

0.7591 inches

Shank Style:

Err-090

Head Major Diameter:

Between 1.044 inches and 1.128 inches

Tip Diameter:

Between 0.6163 inches and 0.6230 inches

Lubrication:

Dry film and cetyl alcohol

End Application:

B1-bacft

Grip Length:

Between 3.177 inches and 3.192 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

0.6250 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

125 ksi min. Shear; 220 ksi min. Tensile; lubrication dry film plus cetyl alsohol per bps171

Material:

Steel comp xm-13

Material Specification:

Ast-5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a



NSN 5320-01-495-8690

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

