

View Online at <https://aerobasegroup.com/nsn/5320-01-495-9554>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.956 inches and 3.990 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.8657 inches

**Shank Style:**

Err-090

**Head Major Diameter:**

Between 1.172 inches and 1.265 inches

**Tip Diameter:**

Between 0.7406 inches and 0.7480 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

B1-bacft

**Grip Length:**

Between 3.240 inches and 3.255 inches

**Thread Qty Per Inch (tpi):**

16

**Thread Size:**

0.7500 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

125 ksi min. Shear; 220 ksi min. Tensile; lubrication dry film plus cetyl alcohol per bps171

**Material:**

Steel comp xm-13

**Material Specification:**

Ast-5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0