## NSN 5320-01-495-9997



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-495-9997 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 4.132 inches and 4.157 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.8657 inches **Shank Style:** Err-090 **Head Major Diameter:** Between 1.284 inches and 1.382 inches **Tip Diameter:** Between 0.7406 inches and 0.7480 inches Lubrication: Dry film and cetyl alcohol **End Application:** B1-bacft **Grip Length:** Between 3.240 inches and 3.255 inches Thready Qty Per Inch (tpi): 16 **Thread Size:** 0.7500 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 125 ksi min. Shear; 220 ksi min. Tensile; lubrication dry film plus cetyl alsohol per bps171 Material: Steel comp xm-13 **Material Specification:** Ast-5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-495-9997

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0