## NSN 5320-01-496-8981

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-496-8981

View Online at https://aerobasegroup.com/nsn/5320-01-496-898
Thread Direction:
Right-hand
Fastener Length:
16.78 millimeters
Head Style:
Err-090
Head Height:
Between 1.15 millimeters and 1.40 millimeters
Width Between Flats:
Between 2.01 millimeters and 2.05 millimeters
Shank Diameter:
Between 4.965 millimeters and 4.990 millimeters
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 7.65 millimeters and 8.15 millimeters
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
9.0 millimeters
Thread Size:
5.0 millimeters
Thread Pitch In Millimeters:
0.80
Thread Tolerance Class:
4h external
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
294, cage 73197 mfr ref single treatment response
Thread Series Designator:
M
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No.

No

## NSN 5320-01-496-8981

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

