NSN 5320-01-497-1935



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-497-1935 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.228 inches and 0.230 inches **Head Major Diameter:** 0.311 inches **Expansion Device:** Threaded stem **End Application:** Cbr+ecp-904; f/a-18 hornet **Grip Length:** Between 0.220 inches and 0.281 inches **Features Provided:** Self-locking Min. Tensile Strength (psi): 1250 pounds per square inch **Shear Strength:** 4600 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Visu-lok, fastener, blind internally threaded, external sleeve titanium 100 degree reduced flush head, self locking 1/32 inch oversize Material: Stainless steel sleeve **Material Specification:** Sae-ams4928 assn standard 1st material response nut or sae-ams4967 assn standard 2nd material response nut **Surface Treatment:** Passivate sleeve **Surface Treatment Specification:** Sae-ams-qq-p-35 assn standard all treatment responses sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A040a0