NSN 5320-01-497-1936

Blind Rivet - Page 1 of 1



/iew Online at https://aerobasegroup.com/nsn/5320-01-497-1936

view Online at https://aerobasegroup.com/nsn/5320-01-497-1936
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.228 inches and 0.230 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.311 inches
Expansion Device:
Threaded stem
End Application:
Cbr+ecp-904; f/a-18 hornet
Grip Length:
Between 0.282 inches and 0.344 inches
Features Provided:
Self-locking
Min. Tensile Strength (psi):
1250 pounds per square inch
Shear Strength:
4600 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Visu-lok, fastener, blind internally threaded, external sleeve titanium 100 degree reduced flush head, self locking 1/32 inch oversize
Material:
Stainless steel sleeve
Material Specification:
Sae-ams4928 assn standard 1st material response nut or sae-ams4967 assn standard 2nd material response nut
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Sae-ams-qq-p-35 assn standard all treatment responses sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A040a0