

View Online at <https://aerobasegroup.com/nsn/5320-01-497-2870>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.269 inches and 0.291 inches

**Head Major Diameter:**

0.405 inches

**Expansion Device:**

Threaded stem

**End Application:**

Cbr+ecp-904; f/a-18e/f hornet aircraft

**Grip Length:**

Between 0.282 inches and 0.344 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

1960 pounds per square inch

**Shear Strength:**

7900 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Visu-lok fastener, blind, internally threaded, external sleeve

**Heat Treatment:**

Annealed nut

**Material:**

Stainless steel sleeve

**Material Specification:**

Sae-ams4928 assn standard 1st material response nut or sae-as-4967 assn standard 2nd material response nut

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Sae-ams qq-p-35 assn standard all treatment responses sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0