NSN 5320-01-497-2870

Blind Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-497-2870

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.269 inches and 0.291 inches
Head Major Diameter:
0.405 inches
Expansion Device:
Threaded stem
End Application:
Cbr+ecp-904; f/a-18e/f hornet aircraft
Grip Length:
Between 0.282 inches and 0.344 inches
Features Provided:
Self-locking
Min. Tensile Strength (psi):
1960 pounds per square inch
Shear Strength:
7900 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Visu-lok fastener, blind, internally threaded, external sleeve
Heat Treatment:
Annealed nut
Material:
Stainless steel sleeve
Material Specification:
Sae-ams4928 assn standard 1st material response nut or sae-as-4967 assn standard 2nd material response nut
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Sae-ams qq-p-35 assn standard all treatment responses sleeve
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: