NSN 5320-01-497-4351

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Flush countersunk

Width Between Flats:

Between 0.538 inches and 0.558 inches

Between 0.0791 inches and 0.0806 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-497-4351

Shank Diameter:
Between 0.2177 inches and 0.2182 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.294 inches and 0.301 inches
Lubrication:
Solid film or cetyl alcohol
End Application:
F/a-18 e/f
Grip Length:
0.193 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Surface roughness per asme b46-1
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-497-4351

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0