## NSN 5320-01-497-4453

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-497-4453



### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.363 inches and 1.383 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

Aircraft, hornet, f/a-18

#### Grip Length:

Between 0.933 inches and 0.948 inches

#### **Thread Size:**

0.2500 inches

#### **Countersink Angle:**

100.0 degrees

#### Material:

Steel comp xm-13

#### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-497-4453

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

