# NSN 5320-01-497-4896

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-497-4896

Head	Stv	ρ.

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### **Shank Diameter:**

Between 0.2016 inches and 0.2026 inches

## **Head Major Diameter:**

Between 0.2966 inches and 0.3016 inches

### **Expansion Device:**

Threaded stem

### Lubrication:

Cetyl alcohol and wax and solid film

### **End Application:**

Aircraft, hornet, f/a-18

### **Grip Length:**

Between 0.157 inches and 0.219 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

# **Material Specification:**

Qq-s-763 federal specification single material response sleeve or ams 5639 assn standard single material response sleeve or ams 5641 assn standard single material response sleeve

# **Surface Treatment:**

Passivate sleeve and cadmium sleeve

## **Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response bolt

# Shelf Life:

N/a

## **Unit Of Measure:**

--

### **Demilitarization:**

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-6758 spec.