NSN 5320-01-497-5095

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-497-5095

Head	Stv	le:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Expansion Device:

Threaded stem

Lubrication:

Cetyl alcohol and wax and solid film

End Application:

Aircraft, hornet, f/a-18

Grip Length:

Between 0.282 inches and 0.344 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification single material response sleeve or ams 5639 assn standard single material response sleeve or ams 5641 assn standard single material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response bolt

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.