

View Online at <https://aerobasegroup.com/nsn/5320-01-497-7882>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.802 inches and 0.822 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3422 inches and 0.3432 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.5001 inches and 0.5051 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.307 inches and 0.317 inches

Thread Size:

0.312 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.