NSN 5320-01-498-3426

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-498-3426 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.364 inches and 0.384 inches **Head Style:** Err-090 **Head Height:** Between 0.045 inches and 0.060 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style:** Pin rivet, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol **Grip Length:** 0.062 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 1760 double pounds per square inch **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-I-37132 military specification single treatment response **Thread Series Designator:** Unjc Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-498-3426

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-37132 spec.