NSN 5320-01-499-5440

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-499-5440 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.7395 inches and 0.7595 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol **End Application:** Apache helicopter **Grip Length:** Between 0.4325 inches and 0.4425 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 4300 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-499-5440

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0