NSN 5320-01-499-5655

Solid Rivet - Page 1 of 1

A040a0



| View Online at https://aerobasegroup.com/nsn/5320-01-499-5655 |
|--|
| Fastener Length: |
| Between 0.635 inches and 0.645 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.1860 inches and 0.1895 inches |
| Shank Style: |
| Tapered hollow |
| Head Major Diameter: |
| 0.3016 inches |
| Shank End Hole Diameter: |
| Between 0.151 inches and 0.161 inches |
| Hole Depth: |
| 0.078 inches |
| End Application: |
| Fwd fuselag 1; aircraft, eagle f-15 |
| Hardness Rating: |
| 24.0 rockwell c and 31.0 rockwell c |
| Shear Strength: |
| 85000 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| Ams 5734 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |