NSN 5320-01-499-5865

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-499-5865 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.678 inches and 0.688 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Expansion Device:** Threaded sleeve **Grip Length:** Between 0.678 inches and 0.688 inches **Hardness Rating:** 49.0 rockwell c **Thread Size:** 0.312 inches **Shear Strength:** 5380 double pounds per square inch **Special Features:** Head is chamferred 0.031 inches at 45 degrees Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-416, type2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-499-5865

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|---|----|----|-----|-----|-------------|---|----|
| n | em | ш | 112 | riz | 2 †1 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.