

View Online at <https://aerobasegroup.com/nsn/5320-01-499-8067>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.590 inches and 2.610 inches

Head Style:

Err-090

Head Height:

Between 0.228 inches and 0.238 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.6699 inches and 0.6709 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.955 inches and 0.990 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10 thunderbolt

Grip Length:

Between 1.745 inches and 1.755 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

41000 pounds per square inch

Thread Size:

0.625 inches

Shear Strength:

67200 double pounds per square inch

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 assn standard 1st material response or mil-s-5626 assn standard 2nd material response or mil-s-6049 assn standard 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.