

View Online at <https://aerobasegroup.com/nsn/5320-01-500-6942>

**Head Style:**

Hexagon

**Head Height:**

0.135 inches

**Shank Diameter:**

Between 0.2470 inches and 0.2490 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Cetyl alcohol or paraffin wax or dry film

**Grip Length:**

Between 0.845 inches and 0.906 inches

**Width Across Flats:**

Between 0.367 inches and 0.375 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

2100 pounds per square inch

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Shear Strength:**

7770 double pounds per square inch

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5626 assn standard 2nd material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response bolt

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.