

View Online at <https://aerobasegroup.com/nsn/5320-01-500-9471>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.450 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

Seaking, mk48, hi-shear corporation

Grip Length:

0.125 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty i, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.