# NSN 5320-01-501-7653

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.097 inches and 2.117 inches

# Head Style:

Straight pan

# Head Height:

0.078 inches

#### Width Between Flats:

0.158 inches

#### Shank Diameter:

0.374 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.565 inches

#### Lubrication:

Solid film and cetyl alcohol

#### **End Application:**

F-18 e/f

## Grip Length:

1.562 inches

#### Thready Qty Per Inch (tpi):

24

# Thread Size:

0.375 inches

#### **Criticality Code Justification:**

Agav

#### **Product Name:**

(inavy) pin - rivet, threaded, shear, protruding head, hex point drive

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response

# Surface Treatment:

Anodize

## **Surface Treatment Specification:**

Ti-shear iii mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-501-7653

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

