NSN 5320-01-501-8429

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-501-8429 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.815 inches and 0.835 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches **Shank Diameter:** Between 0.1810 inches and 0.1840 inches **Shank Style:** Stump **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Expansion Device:** Threaded sleeve Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.505 inches **Thread Size:** 0.190 inches **Special Features:** Head is chamferred 0.031 inches at 45 degrees Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-501-8429

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.