# NSN 5320-01-502-1313

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-502-1313



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.380 inches and 1.505 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

0.104 inches

Shank Diameter:

Between 0.2630 inches and 0.2650 inches

#### Shank Style:

Pin rivet, threaded

#### Head Major Diameter:

0.507 inches

# End Application:

F-22

### Grip Length:

Between 0.376 inches and 0.438 inches

## Thready Qty Per Inch (tpi):

48

## Min. Tensile Strength (psi):

160000 pounds per square inch

### **Thread Size:**

0.216 inches

### Shear Strength:

95000 single pounds per square inch

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### **Product Name:**

Fastener

### Material:

Titanium alloy

## **Thread Series Designator:**

Uns

## Shelf Life:

N/a

## Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-502-1313

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

