NSN 5320-01-502-1461

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-502-1461 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.675 inches and 1.695 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Solid film **End Application:** Aircraft, thunderbolt ii, a-10 **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 34300 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 49100 double pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-502-1461

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0