# NSN 5320-01-502-1461

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-502-1461



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.675 inches and 1.695 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.178 inches and 0.188 inches

### Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.4985 inches and 0.4995 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Solid film

End Application:

Aircraft, thunderbolt ii, a-10

# Grip Length:

Between 0.995 inches and 1.005 inches

### Thready Qty Per Inch (tpi):

20

### Min. Tensile Strength (psi):

34300 pounds per square inch

### Thread Size:

0.500 inches

### Shear Strength:

49100 double pounds per square inch

### Material:

Steel comp xm-13

### **Material Specification:**

Ams 5629 assn standard single material response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-502-1461

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

