## NSN 5320-01-502-1485

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-502-1485 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.710 inches and 1.730 inches **Head Style:** Err-090 **Head Height:** Between 0.200 inches and 0.210 inches Width Between Flats: Between 0.2520 inches and 0.2555 inches **Shank Diameter:** Between 0.5605 inches and 0.5615 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.842 inches and 0.877 inches Lubrication: Solid film **End Application:** Aircraft, thunderbolt ii, a-10 **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 43500 pounds per square inch **Thread Size:** 0.5625 inches **Shear Strength:** 62100 double pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-502-1485

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0