## NSN 5320-01-502-3228

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-502-3228 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 1.188 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.302 inches and 0.306 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.3125 inches **Shear Strength:** 95000 single pounds per square inch Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type i, class 2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5320-01-502-3228

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.