# NSN 5320-01-502-4705

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-502-4705

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.428 inches and 1.448 inches

# Head Style:

Straight pan

## **Head Height:**

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.127 inches and 0.129 inches

## Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.475 inches and 0.505 inches

## Grip Length:

Between 0.933 inches and 0.943 inches

# Thready Qty Per Inch (tpi):

A24

## Thread Size:

0.312 inches

## **Special Features:**

Head configuation has a 45 degrees chamfered edge. Dimensions provided by a standard part document st3m761

Material:

Steel

## Material Specification:

Ams 5629, ph13-8mo assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-502-4705

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

